


# 115 Series

A24 - Ceiling to Ceiling

A18 - Wall to Ceiling



**Movement Rating ± 50%**

Product  
Guide



- ▶ Model **115** frame pop rivets to T-Bar profile in suspended ceiling system
- ▶ Bellows seal allows for seismic movement
- ▶ Standard seal colors: black, beige, gray, off white and bright white. Custom colors available upon request.

Application	System	W		H1		H2		S		B		Movement +/-			
		Joint Width		Frame Height 1		Height 2		Sightline		Blockout		Horizontal		Vertical	
		US	mm	US	mm	US	mm	US	mm	US	mm	US	mm	US	mm
Ceiling/Ceiling	115-A24-050	2"	51	*	*	*	*	2"	51	*	*	1"	25	1"	25
	115-A24-075	3"	76	*	*	*	*	3"	76	*	*	1 1/2"	38	1 1/2"	38
	115-A24-100	4"	102	*	*	*	*	4"	102	*	*	2"	51	2"	51
	115-A24-125	5"	127	*	*	*	*	5"	127	*	*	2 1/2"	64	2 1/2"	64
	115-A24-150	6"	152	*	*	*	*	6"	152	*	*	3"	76	3"	76
Wall/Ceiling	115-A18-050	2"	51	*	*	*	*	2"	51	*	*	1"	25	1"	25
	115-A18-075	3"	76	*	*	*	*	3"	76	*	*	1 1/2"	38	1 1/2"	38
	115-A18-100	4"	102	*	*	*	*	4"	102	*	*	2"	51	2"	51
	115-A18-125	5"	127	*	*	*	*	5"	127	*	*	2 1/2"	64	2 1/2"	64
	115-A18-150	6"	152	*	*	*	*	6"	152	*	*	3"	76	3"	76


May be available in larger widths, please contact InPro Corporation for more details.

IPC.1517/REV.8

# 115 Series

## Acoustical Ceiling Systems

115-A24  
Ceiling/Ceiling  
(2" (50mm) system shown)



115-A18  
Ceiling/Wall  
(2" (50mm) system shown)

