

# Vinylseal

## Color Matched Caulk



Item	Description
580	10.5oz Cartridge
561	Caulk Gun

**BEFORE HANDLING, READ PRODUCT AND MATERIAL SAFETY DATA SHEETS FOR DETAILED USE AND HEALTH INFORMATION.** SILICONIZED ACRYLIC LATEX GRADE PVC JOINT SEALANT INTENDED FOR USE ON IPC RIGID VINYL SHEET AND PROFILE PRODUCTS.

**IMPORTANT:** This product may stain adjacent walls or wall-covering. Masking of these areas may be necessary. Test an inconspicuous area to see if staining will occur.

**USE LIMITATIONS:** Not for underwater use; whole joint size not to exceed 1/4"; do not take internally; keep out of reach of children.

**NOTICE TO PURCHASER:** Manufacturers and Sellers liability for damages hereunder shall not exceed the purchase price of the goods used. Manufacturers and Seller warrant only that the goods will be free from defects in material. The foregoing warrant is in lieu of all other warranties, expressed or implied, including those of merchantability of fitness for any purpose not expressly set forth herein. No liability is assumed by Manufacturer or Seller except as expressly stated herein. In no event shall damages arising out of or in connection with the use of this product by user, buyer's user, or any other person.

Two year shelf life: Stored at 40-90°F in a dry place

Coverage: approximately 25 linear ft. (1/4" bead)

1. Surfaces to be sealed must be free of dirt, dust, oil, wax and other such substances.
2. Caulk should be applied at room temperature, allowing at least 24 hours to fully cure.
3. Applying caulk to IPC profile products that are mounted to an aluminum retainer: Remove vinylcover and apply masking tape where joint will appear. Snap on vinyl cover and proceed to Step 4.
4. Use masking tape or similar to control caulk in desired joint area. This will ease in clean-up, lessen joint size, and eliminate possible staining to wall or wallpaper.
5. Cut spout to desired bead size. NOTE: Apply caulk directly to joint. Cut spout at 45° angle for faster and easier application.
6. As required, use moistened fingers or putty knife and tool within 20 minutes. Remove masking tape.
7. Clean-up any excess with a damp cloth before caulk fully cures.

IPC.484/REV.3