

Clickeze® Window Top Treatments

KELSEY

- 14" drop at center
- 3-1/2", 6" or 8" returns
- Velcro attachment
- Bottom band with contrasting fabric available
- Easily removed for cleaning
- L-bracket installation
- Ceiling mount bracket available
- Hardware included
- Hardware for wall attachments (by others)



SHEFFIELD

- 14" panel drop, 12" pleat drop
- 3-1/2", 6" or 8" returns
- Velcro attachment
- Bottom band with contrasting fabric available
- Easily removed for cleaning
- L-bracket installation
- Ceiling mount bracket available
- Hardware included
- Hardware for wall attachments (by others)



LUDINGTON

- 14" drop at center
- 3-1/2", 6" or 8" returns
- Velcro attachment
- Bottom band with contrasting fabric available
- Easily removed for cleaning
- L-bracket installation
- Ceiling mount bracket available
- Hardware included
- Hardware for wall attachments (by others)



Single Style Shown

IPC.605/Rev.4

Clickeze® Window Top Treatments

PENNANT

- 16" drop at center, 14" drop at sides
- 3-1/2", 6" or 8" returns
- Velcro attachment
- Bottom band with contrasting fabric available
- Easily removed for cleaning
- L-bracket installation
- Ceiling mount bracket available
- Hardware included
- Hardware for wall attachments (by others)



INVERTED BOX PLEAT

- 14" drop at center
- 3-1/2", 6" or 8" returns
- Velcro attachment
- Bottom band with contrasting fabric available
- Easily removed for cleaning
- L-bracket installation
- Ceiling mount bracket available
- Hardware included
- Hardware for wall attachments (by others)



EXPANDED BOX PLEAT

- 14" drop at center up to 120" width, 16" drop at center over 120"
- 3-1/2", 6" or 8" returns
- Bottom band with contrasting fabric available
- Velcro attachment
- Easily removed for cleaning
- L-bracket installation
- Ceiling mount bracket available
- Hardware included
- Hardware for wall attachments (by others)



Single Style Shown

Inprocorp.com • 800.222.5556 • 262.679.9010

World Headquarters S80 W18766 Apollo Drive, Muskego, WI 53150 USA

CLICKEZE®
PRIVACY SYSTEMS
A DIVISION OF INPRO®

Clickeze® Window Top Treatments

Suggested Specifications

PART 1 - GENERAL

1.01 SUMMARY

A. Top Treatment

1.02 SECTION INCLUDES

A. Top Treatment

1.03 REFERENCES

A. National Fire Protection Association (NFPA)

1.04 SYSTEM DESCRIPTION

A. Performance Requirements: Provide top treatment fabrics that conform to the following requirements of regulatory agencies and the quality control of Clickeze® Privacy Systems, Inpro Corporation.

1. Fire Performance Characteristics: Provide top treatment fabrics that conform with NFPA 701, Fire Tests or Flame and Resistant Textiles and Films.

1.05 SUBMITTALS

A. Product Data: Manufacturer's printed product data for each type of top treatment board specified.

B. Fabric Samples: Swatch cards of fabric samples illustrating fabric color and weave.

C. Manufacturer's Care Instruction: Printed care instructions for each top treatment board.

1.06 DELIVERY, STORAGE AND HANDLING

A. Deliver materials in unopened factory packaging to the jobsite.

B. Inspect materials at delivery to assure that specified products have been received.

C. Store in original packaging in a climate controlled location away from direct sunlight.

1.07 PROJECT CONDITIONS

A. Environmental Requirements: Products must be installed in an interior climate controlled environment.

1.08 WARRANTY

A. Standard Clickeze® Limited Warranty against material and manufacturing defects.

PART 2 - PRODUCTS

2.01 MANUFACTURER

A. Acceptable Manufacturer:

Clickeze® Privacy Systems, Inpro Corporation,
PO Box 406 Muskego, WI 53150 USA;
Telephone: 800.222.5556, Fax: 888.715.8407,
www.inprocorp.com

B. Substitutions: Not permitted

C. Provide all top treatment boards from a single source.

2.02 MATERIALS

A. Top treatment

1. Fabric: Provide 100% polyester fabric that is flame retardant.

2.03 FINISH AND COLOR

A. Top Treatment Fabric: Select solid or patterned fabric from manufacturer's standard selection.

2.04 FABRICATION

A. Top Treatment

1. Provide Kelsey Top Treatment to width required for window.

a. Top treatment shall have a 14" drop at the center.

b. Returns shall be 3-1/2", 6" or 8".

c. Optional bottom band shall have contrasting fabric.

d. Mounting board shall be installed with L-bracket or ceiling mount bracket. Fasteners to attach

L-brackets to the wall shall be supplied by others.

e. Attachment to the mounting board shall be with Velcro, which allows for easy removal.

2. Provide Sheffield Top Treatment to width required for window.

a. Top treatment shall have a 14" panel drop, 12" pleat drop.

b. Returns shall be 3-1/2", 6" or 8".

c. Optional bottom band shall have contrasting fabric.

d. Mounting board shall be installed with L-bracket or ceiling mount bracket with supplied fasteners.

e. Attachment to the mounting board shall be with Velcro, which allows for easy removal.

3. Provide Ludington Top Treatment to width required for window.

a. Top treatment shall have a 14" drop at the center.

b. Returns shall be 3-1/2", 6" or 8".

c. Optional bottom band shall have contrasting fabric.

d. Mounting board shall be installed with L-bracket or ceiling mount bracket. Fasteners to attach

L-brackets to the wall shall be supplied by others.

e. Attachment to the mounting board shall be with Velcro, which allows for easy removal.

4. Provide Pennant Top Treatment to width required for window.

a. Top treatment shall have a 16" drop at the center.

b. Returns shall be 3-1/2", 6" or 8"

c. Optional bottom band shall have contrasting fabric.

d. Mounting board shall be installed with L-bracket or ceiling mount bracket. Fasteners to attach

L-brackets to the wall shall be supplied by others.

e. Attachment to the mounting board shall be with

Velcro, which allows for easy removal.

5. Inverted Box Pleat Top Treatment to width required for window.

a. Top treatment shall have a 14" drop at the center.

b. Returns shall be 3-1/2", 6" or 8".

c. Optional bottom band shall have contrasting fabric.

d. Mounting board shall be installed with L-bracket or ceiling mount bracket. Fasteners to attach

L-brackets to the wall shall be supplied by others.

e. Attachment to the mounting board shall be with Velcro, which allows for easy removal.

6. Provide Expanded Box Pleat Top Treatment to width required for window.

a. Top treatment shall have a 14" drop on widths up to

120", and a 16" drop at center on widths over 120".

b. Returns shall be 3-1/2", 6" or 8".

c. Optional bottom band shall have contrasting fabric.

d. Mounting board shall be installed with L-bracket or ceiling mount bracket. Fasteners to attach

L-brackets to the wall shall be supplied by others.

e. Attachment to the mounting board shall be with Velcro, which allows for easy removal.

PART 3 - EXECUTION

3.01 EXAMINATION

A. Examine areas and conditions in which the top treatment will be installed.

1. Complete all finishing operations, including painting, before beginning installation of cubicle tracking system materials.

2. Verify that surfaces and above ceiling supports are ready to receive work.

3.02 PREPARATION

A. General: Prior to installation, clean substrate to remove dust, debris, and loose particles.

3.03 INSTALLATION

A. General: Locate the top treatment as indicated on the approved detail drawing for the appropriate substrate and in compliance with the installation instructions.

3.04 CLEANING

A. At completion of the installation, remove any debris and clean surfaces in accordance with the Clickeze® clean-up and maintenance instructions.